


MOUNTING OPTION
STYLE : 2



MOUNTING OPTION
STYLE : 1

SIDE	DATE	DESCRIPTION	APPROVER
△			

NOTES:

- 1>. CONTACT HEIGHT FOR PIN# 8,18, 28 IS. 4.70. BALANCE OF CONTACTS. 5.46.
- 2>. MATERIALS & PLATING:
HOUSING: PBT+30%GF
BLACK, UL 94V-0
CONTACT: BRASS, PLATING SEE NOTE6.
SHELL: STEEL, FRONT SHELL: NICKEL PLATED
BACK SHELL: TIN PLATED
- 3>. MECHANICAL:
MATING FORCE: 10 LB. (4.5kg) MAXIMUM.
UNMATING FORCE: 2.2 LB. (1kg) MINIMUM
8.8 LB. (4kg) MAXIMUM.
- 4>. RoHS PRODUCT
- 5>. ELECTRICAL:
VOLTAGE RATING: 40VAC R.M.S.

CURRENT RATING: 1.5 AMP.
INSULATION RESISTANCE:
1000 MEGOHMS MIN.
WITHSTANDING VOLTAGE:
500 VAC/1 MINUTE
CONTACT RESISTANCE:
20 MILLIOHMS MAX. (INITIAL)
- 6>. ENVIRONMENTAL:
TEMPERATURE RANGE:
-20 °C TO +85 °C
- 7>. ORDER INFORMATION:
931-462205-1XX

Gold Plated for contact

01:30U" 02-15U"

电话(tel)	0755-89488808	公差					
传真(fax)	0755-89488865	.0±0.38	.0° ±1.0°				
		.00±0.20	.00° ±0.5°				
		.000±0.05	.000° ±0.1°				
比例(scale)	1 : 1	日期 (date)		单位(units)	mm	图名(name)	EVC 30+5PIN FEMALE Connector
页次(sheet)	A / 1	绘图 (draw)		颜色 (shaded)		图号(draw number)	
版次(rev.)	A	审核 (ch'k)		材料(mt'l)		料号 (Part number)	931-462205-1XX
视图(view)	⊕	核准(app'd)		处理(finish)		档档 (File Name)	E:\工程资料\003-draw\成品图